



Service Bulletin

85A

November, 1967

Mounting RT-367 Tiller on Models 875, 876, 1075, 1076 & 1276

Supplement to RT-367 Tiller Parts List & Instructions

This bulletin corrects, replaces and supercedes Service Bulletin #85, dated June, 1967. The original bulletin should be destroyed.

The following supplementary information is required to mount the RT-367 tiller on the above models.

1. Rework #6136 brake lever assembly as shown in print by cutting the handle section off next to the weld or replace with a new #7016 brake lever assembly.
2. Install new brake handle #7011 and #6129 grip.
3. Notch out belt guard assembly as shown in print.

NOTE: Part #6133 link will not be reused.
Component parts should be ordered as required.

Atwood S. Kidder

Atwood S. Kidder
Customer Relations Manager

ASK/rr

INSTALLATION OF RT 367 TILLER ON 875, 876, 1075, 1076 & 1276 TRACTORS

REQUIRES # 7011 BRAKE HANDLE-
ASSY & 6129 HANDLE GRIP

6133-WILL NOT USE

RE-USE 933503-4

6136 REWORK OR
REPLACE WITH 7016

RE-USE 911400

RE-USE MW-8821

RE-USE 6134

RE-USE 92009-4

REWORK BY CUTTING
OFF BEHIND WELD

RE-USE 920011-4

RE-USE 5701
NOTCH BELT GUARD

