



Service Bulletin

87

December, 1967

USE OF HY-6, PT-6 AND AC-675 ON 1968 MODELS

HY-6 Hydraulic Unit

The HY-6 hydraulic lift can be substituted for the 8-4111 hydraulic lift with the addition of the following parts:

1-7675 Foot Rest Bracket
1-908032-4 Hex Bolt
1-915663-4 Hex Nut

1-933505-4 Hair Pin Cotter
1-Instruction Form No. 379

PT-6 Power Take Off

The power take off PT-6 can be substituted for the 8-3111 power take off by removing and adding the following parts:

Remove


1-6653 Assembly Plate & Rod

Add

1-7661 Assembly Plate & Rod
1-909865-6 Set Screw Nylock
1-Instruction Form No. 384

AC-675 Cultivator

The AC-675 two section cultivator can be substituted for the 7-1721 cultivator by altering the two front inner shovel standards, as shown in the accompanying sketch. The standards are shortened by 1 1/4" which allows the standards to work under the running board. After altering, these standards become the same as the new 7659 standards.



Proper Method of Adjusting Standards and Shovel Assemblies

1. Place shovel standards on front cultivator frame with standards as high as possible.
2. Mount the rear standards on the rear frame as low as possible.
3. Place 5581 lift link assembly in the second hole of tractor lift.

This method of adjusting standards will give equal penetration of the shovels to a depth of three (3) inches.

A. S. Kidder

ASK/rr

A. S. Kidder
Customer Relations Manager